



Anker SOLIX X1

Hybrid Single-Phase Energy Storage System

| System Parameters

Battery Module	× 1	× 2	× 3	× 4**	× 5**	× 6**
Energy Capacity	5 kWh	10 kWh	15 kWh	20 kWh	25 kWh	30 kWh
Weight*	73.5 kg	124.5 kg	175.5 kg	232 kg	283 kg	334 kg
W×H×D Dimensions (mm)	670 × 765 × 150	670 × 1,125 × 150	670 × 1,485 × 150	670 × 1,485 × 150 670 × 482 × 150	670 × 1,485 × 150 670 × 842 × 150	670 × 1,485 × 150 670 × 1,202 × 150

*Includes floor mounting base and top cover.
**Two column installation.

| Battery Module

	BPaettrefroyrmance Specifications
Battery Energy*	5 kWh
Battery Type	Li-ion (LFP)
Battery Voltage Range	350 - 550 VDC
Maximum Charge / Discharge Power	3 kW
Maximum Charge / Discharge Current	7.6 A
	Other
W×H×D Dimensions (mm)	670 × 360 × 150
Weight	51 kg
Ingress Protection Rating	IP65
Operating Temperature	-20°C to 55°C
Maximum Operating Altitude	Up to 4,000 m, Power Derates from 2,000 m
Warranty	10 Years**
	Compliance Information
Certifications	IEC 62619, IEC 62040-1, VDE-AR-E 2510-50, UN38.3

*The initial capacity (design capacity) of an expansion battery is 5 kWh. The actual capacity may vary depending on environmental conditions, such as temperature, transportation methods, and storage conditions.
**Refer to Anker SOLIX X1 Home Energy Storage System Warranty policy for details.

Email: info@ankersolix.com.tr
Telefon: +90 539 844 04 84

The product specifications and details contained in this brochure are based on preliminary information and are subject to change without notice. The actual product features and specifications may vary upon its o*cial release.

I Power Module

Model	X1-H3.68K-S	X1-H4.6K-S	X1-H5K-S	X1-H6K-S
	Battery Input			
Battery Type	LFP			
Charge Voltage Range	390 - 550 VDC			
Discharge Voltage Range	370 - 500 VDC			
Battery Capacity	5 - 30kWh			
	PV Input			
Max Input Power	7.36 kW	9.2 kW	10 kW	12 kW
Max Input Voltage	600 VDC			
MPPT Voltage Range	80 - 550 VDC			
Start-Up Voltage	60 VDC			
Rated Input Voltage	360 VDC			
Max PV Input Current	16 A			
1sc PV Array Short Circuit Current	20 A			
Number of MPPTs	2			
Number of Strings per MPPT	1			
	AC Output (On-Grid)			
Rated Output Power	3.68 kW	4.6 kW	5 kW	6 kW
Max Output Apparent Power	4 kVA	5 kVA	5.5 kVA	6.6 kVA
Rated Output Voltage	220/230/240 V			
Rated Frequency	50/60 Hz			
Power Factor	0.8 ind - 0.8 cap			
THDI (@Rated Power)	< 2%			
	AC Output (0"-Grid)			
Rated Output Power	3.68 kW	4.6 kW	5 kW	6 kW
Max Output Apparent Power	4 kVA	5 kVA	5.5 kVA	6.6 kVA
Peak Output Apparent Power (Duration)	7,200 VA (10s)	10,000 VA (10s)	10,000 VA (10s)	10,000 VA (10s)
Max Units In Parallel	3			
Rated Output Voltage	220 / 230 / 240 VAC			
Rated Frequency	50/60 Hz			
THDU (@Linear Load)	< 2%			
Switch Time	< 10 ms			
	AC Input			
Max Input Apparent Power	7.2 kVA	10 kVA	10 kVA	10 kVA
	E#ciency			
Max E"ciency	97.6%			
European E"ciency	97.1%			
	Connectivity			
Internet Connectivity	Wi-Fi, Bluetooth, Ethernet, 4G (Optional)			
	Other			
Weight	19 kg			
W×H×D Dimensions (mm)	670 × 335 × 150			
Noise	≤ 30dB*			
Mounting Options	Ground or Wall**			
Operation Temperature	-25°C to 60°C***			
Relative Humidity	0 to 100%			
Max Operating Altitude	Up to 4,000 m, Power Derates from 2,000 m			
Ingress Protection Rating	IP66			
Warranty	10 Years Limited****			
	Compliance Information (More Information Available Upon Request)			
Grid Connection Certifications	VDE-AR-N 4105, DIN VDE V 0124-100 (VDE V 0124-100), CEI 0-21, G99/1-9, C10/C11, NTS 2021 V2.1, UNE 2170021, UNE 217002, AS/NZS 4777.2			
Safety	EN 62109-1, EN 62109-2, AS 60947.3			
EMC	EN IEC 61000-6-1, EN IEC 61000-6-3			

*Tested in Anker laboratory at 1 m distance and typical voltage.
**Additional rack required for wall mounting.
***Power derates once ambient temperature exceeds 45°C.
****Refer to Anker SOLIX X1 Home Energy Storage System Warranty Policy for details.